

### IN THE CLAIMS

This listing of claims replaces all prior listings:

1. (Currently Amended) A method of manufacturing a diffusing reflector comprising the processes of:
  - preparing a substrate;
  - forming a first resin film having photosensitivity on said substrate;
  - providing a gathering of adjacent pillar-shaped bodies isolated from each other through patterning of said resin film with photolithography;
  - deforming gently said adjacent pillar-shaped bodies through a reflow;
  - forming an uneven surface layer having the maximum inclination angle of under  $12^{\circ}$  by coating with a thin layer of a second resin said gently deformed pillar-shaped bodies;
  - covering with the second resin open flat spaces located between said isolated adjacent pillar-shaped bodies to form one concave gap between any two adjacent isolated pillar-shaped bodies so that upper end portions of said any two adjacent isolated pillar-shaped bodies are higher than a lower end portion of said one concave gap in the thickness direction of the diffusing reflector, thereby minimizing an occurrence of a flat surface area on said substrate; and
  - forming a metal film on said uneven surface layer,wherein,
  - said first resin film is patterned by straight connected lines that form a continuous polygonal pattern, said straight lines providing a continuous and substantially uniform gap between thereby formed said polygonal pillar-shaped bodies thereby forming a rectilinear honeycomb-like pattern, and
  - said gap having a size equal to about a minimum resolution of said photolithography, and
  - a thickness of the second resin is about 500nm.
2. (Previously Presented) The method of manufacturing a diffusing reflector as claimed in claim 1, wherein said maximum inclination angle is about  $10^{\circ}$ .

3. (Cancelled)

4. (Previously Presented) The method of manufacturing a diffusing reflector as claimed in claim 1, wherein said reflow process is a heat treatment under the temperature of about 220°C.

5. (Previously Presented) The method of manufacturing a diffusing reflector as claimed in claim 1, wherein gathering of polygonal pillar-shaped bodies isolated from each other by the divided patterning of said first resin film by said photolithography is provided.

6. (Cancelled)